


HORIZONTAL SPLIT CASING PUMPS MODEL HS & HSDS




APPLICATIONS


- Firefighting
- Water Supply
- Textile
- Sugar
- Power
- Air Conditioning
- Irrigation
- · Paper & Pulp
- Mine Drainage

HORIZONTAL SPLIT CASING PUMPS


MODEL HS




PERFORMANCE CURVES:



MODEL HSDS



PERFORMANCE CURVES:



CASING:

Horizontally split volute casing with suction and discharge branches located opposite in line in the

IMPELLER:

Impeller(s) are Dynamically / Hydraulically balanced in both models. Impellers of HS type two stage pumps a mounted back to back for balanced axial thrust.

SHAFT:

Accurately machined and ground from high tensile steel, designed for minimum deflection. Keyways are provided for impeller drive.

SHAFT SLEEVES:

Sleeves are provided to protect the shaft. These are renewable and extend through the stuffing box.

WEAR RINGS:

Renewable Impeller Wear Rings are provided to ensure long impeller life. Casing Wear Rings are provided in HSDS type pumps.

STUFFING BOX:

With suitable gland packing. Mechnical Seals available on request.

FLANGES:

Drilled to ASA Class 150 ANSI B 16.5 standard. Other standards at option.

MATERIAL OF CONSTRUCTION:

Can be offered in different combinations of Cast Iron, Bronze and Phosphor Bronze. Special materials available for handling corrosive liquids.

DIRECTION OF ROTATION:

Clockwise when seen from drive end. Anti-clockwise can be offered.



FLO-RITE ENGINEERING CORPORATION

Office : Gala No. 7, 1st Floor, Janata Industrial Compound,

162, Senapati Bapat Marg, Lower Parel (W), Mumbai - 400 013.

Tel. : (+91-22) 2493 4670, 2498 5208

Fax : (+91-22) 2493 7846
Email : florite@gmail.com
Website : www.flo-ritepumps.com

Factory : Dwarka Industrial Estate, Plot No. 7A,

Near Naik Pada, Valiv Village, Vasai (East), Maharashtra.